

Excel Excite 4 'Galaxy'



Suspension mobility scooter

Equipped with taxi fixation points on frame
Equipped with brake lights

Dashboard with tip touch display left and right single-handed operable, equipped with a horn
Maximum speed 12 km/h (8 mph)
Theft prevention system using ignition key

Removable shopping basket
Including indicators and head and tail lights

Adjustable steering angle, stepless adjustable and can also be folded down completely

Impact-resistant plastic covers

Shock bumper on the front and rear
Suspension on the front wheel with telescopic shock absorber in front fork

Seat equipped with adjustable backrest extender / headrest

Foldable armrest, width, angle and height adjustable

Seat can steplessly rotate 360 degrees, with folding backrest and angle adjustable back

Seat depth adjustable

Standard with removable seat, height adjustable (45 - 55 cm, 4 positions)

Equipped with brake lights

Motor equipped with electro-magnetic brake
Equipped with programmable digital electronics, 'Control Dynamic 'Rhino 160', driving characteristics and speed adjustable
Range up to 35 km by 50 Ah batteries (extendable to 73 Ah batteries)

Easy to adjust rear suspension



Equipped with independent suspension on the front and rear. Also easily adjustable rear suspension.
Standard equipped with anti tip system.



Angle adjustable steering column, stepless and operable from the steering column.
Can also be folded down for transportation.

'Smart mobility solutions'

Standard specifications

Overall width:	65 cm
Height rear:	127 cm
Height front:	110 cm
Overall length:	146 cm*
Seat width:	48½ cm
Seat height:	48 - 58 cm
Guardrail height:	24 - 30 cm
Total seat width:	52 cm
Wheelbase:	97 cm
Ground clearance:	13 cm
Speed:	12 km/h (8 mph)**
Range:	35 km with 50 Ah batteries 50 km with 73 Ah batteries

* Including cover, anti-tip system and (optional) crutch holder
** The maximum speed of the scooter can be electronically adjusted to lower values

Total weight: 127 kg (Depending on the model)
Max. User Weight: 175 kg

Available in colour:



Product complies with crash test EN12184



We have a continual product improvement policy and consequently reserve the right to amend design and specifications without prior notice at any time and without obligation.

All rights reserved. Copyright 2009 Van Os Medical B.V.



Van Os Medical UK Ltd
Corunna House
42-44 Ousegate
Selby
YO9 4NH

Tel.: +44 (0) 1757 701177
Fax: +44 (0) 1757 706011

sales@vanosmedical.com

www.vanosmedical.com

